



ABC Dry Chemical

**Manufactured and Tested to
ANSI/UL Standards
AS & NZ Standards
Amerex is an ISO-9001:2000
Registered Firm**

- ★ Dependable Steel Cylinders
- ★ All Metal Valve Construction
- ★ Easy and less costly to maintain and service
- ★ U/L & U.S. Coast Guard Listed
- ★ Bar Coded Labels

(Temperature Range -53°C to 50°C)

Note: All extinguishers are U.S. Coast Guard approved with bracket listed on U.L. label.

Stored Pressure



Additional white band in AS/NZ



ABC or Multi-Purpose extinguishers utilize a specially fluidized and siliconized mono ammonium phosphate dry chemical. It chemically insulates Class A fires by melting at approximately 177°C and coats surface to which it is applied. It smothers and breaks the chain reaction of Class B fires and will not conduct electricity back to the operator.

Available in Wheeled and Stationary extinguishers.

6 YEAR WARRANTY

Specifications	ABC Dry Chemical										
Valves	Aluminium						Brass, Chrome plated (No Alloy)				
Size and Capacity	1.13kg	2.25kg	2.25kg	2.27kg	4.5kg Tall	9kg	2.25kg	2.27kg	4.5kg Short	4.5kg Tall	9kg
Application	Nozzle	Hose and Nozzle				Hose and Nozzle					
Model Number	B417 / B417T	B500 / B500T	B402 / B402T	B443	B456	A411	B424	B461	419	B441	423
U/L Rating	1A:10B:C	2A:10B:C	3A:40B:C	3A:40B:C	4A:80B:C	20A:120B:C	2A:10B:C	3A:40B:C	4A:80B:C	4A:80B:C	20A:120B:C
AS/NZ Model	A-B417TAS	A-B500AS B500TAS	N/A	N/A	A-B456AS	A-411AS	A-B424AS	N/A	A-419AS	A-668AS	A-423AS
AS/NZ Rating	1A:20B:E	2A:40B:E			4A:60B:E	6A:80B:E	2A:40B:E		4A:80B:E	4A:80B:E	6A:80B:E
SSL Listing					Yes	Yes				Yes	
Shipping Wt.	2.4kg / 2.5kg	4.2kg / 4.3kg	4.2kg / 4.3kg	5.8kg	8.2kg	17.2kg	4.8kg	6.2kg	8.6kg	8.6kg	17.7kg
Height	394mm	387mm	387mm	406mm	508mm	591mm	394mm	413mm	450mm	521mm	607mm
Width	146mm	184mm	184mm	197mm	197mm	273mm	203mm	216mm	241mm	222mm	260mm
Depth	76mm	108mm	108mm	127mm	127mm	178mm	108mm	127mm	152mm	127mm	178mm
Range	2.75m - 4.5m	3.7m - 5.5m	3.7m - 5.5m	4.6m - 6.4m	4.6m - 6.4m	4.6m - 6.4m	3.7m - 5.5m	4.6m - 6.4m	4.6m - 6.4m	4.6m - 6.4m	4.6m - 6.4m
Discharge time (sec)	10	14	14	14.5	20	30	14	14	22	20	30
Available with chrome plated cylinder	YES	YES	YES		YES					YES	
F.M Approved	YES	YES		YES	YES	YES		YES	YES	YES	YES
Standard Bracket	Wall / Vehicle-Marine			Wall			Wall				