



# Carbon Dioxide

*Manufactured and Tested to  
ANSI/UL Standards*

*Amerex is an ISO-9001:2000  
Registered Firm*

- ★ Rust free aluminum cylinders - up to 30% lighter than steel cylinders
- ★ All Metal Valve Construction
- ★ Low magnetic - meets many hospital medical equipment requirements
- ★ Bar Coded Labels

(Temperature Range -40°F to 120°F)

Note: All extinguishers are U.S. Coast Guard approved with bracket listed on U.L. label



SPECIFICATIONS	CARBON DIOXIDE			
	5	10	15	20
Size & Capacity (lbs.)	5	10	15	20
Application	Horn	Hose & Horn		
Model Number	322	330	331	332
U/L Rating	5B:C	10B:C	10B:C	10B:C
Shipping Weight (lbs.)	14	28¾	37¾	50¾
Height (in.)	17¾	24	30	30
Width (in.)	8¾	12	12	13
Depth (Diam. - in.)	5¾	7	7	8
Range (ft.)	3-8			
Discharge Time (sec.)	10	10	12½	19
F. M. Approved	Yes			
Standard Bracket	Wall			

**Carbon Dioxide** is discharged as a white cloud of "snow" which smothers a fire by eliminating oxygen. It is effective for Class B flammable liquids and is electrically non-conductive. Carbon Dioxide is a clean, non-contaminating, odorless gas.

**Also available in 50 and 100 lb.  
wheeled extinguishers**

**U.L. LISTED - 6 YEAR WARRANTY**