



HIGH PERFORMANCE

Dry Chemical

**Manufactured and Tested to
ANSI/UL Standards
AS/NZ Standards
Amerex is an ISO-9001:2000
Registered Firm**

EXTRA FEATURES:

- ★ Superior Range (Vertical & Horizontal)
- ★ High (240 PSI) Operating Pressure
- ★ Choice of Chemicals
ABC Multi Purpose, Regular, Purple K
- ★ Select *Fast Flow* for:
High Flow Rate
Fast Discharge
Quicker Knockdown
More Operator Protection
- ★ Select Compliance Flow for:
Long Range
Highest U.L. Ratings
- ★ Epoxy Painted GALVANIZED STEEL Cylinders
(The best corrosion protection available anywhere)
- ★ Protective Rubber Foot Rings
- ★ All Metal Valve Construction
- ★ Gauge Guards
- ★ Bar Coded Labels
(Temperature Range -53°C to 55°C)

Note: All extinguishers are U.S. Coast Guard approved with bracket listed on U.L. label

Stored Pressure



AS & NZ Additional White band

HIGH PERFORMANCE extinguishers are the ultimate choice in fire extinguishers for high hazard, frequent use and extreme environment applications. Economical - less initial cost, lower maintenance costs and greater reliability than cartridge operated extinguishers.

Available in 113Kg Wheeled and Stationary extinguishers.

12 YEAR WARRANTY

Specifications	High Performance - ABC, Regular, Purple K Dry Chemical														
Type	Fastflow									Compliance Flow					
Agent	ABC			Regular			Purple K			ABC			Purple K		
Application	Nozzle									Hose and Nozzle					
Size & Capacity	6kg	9kg	13.6kg	9kg	13.6kg	6kg	9kg	9kg	13.6kg	6kg	9kg	13.6kg	6kg	9kg	13.6kg
Model Number	594	581	567	582	568	595	580	584	569	592	564	589	599	566	591
U/L Rating	2A:40B:C	4A:40B:C	4A:40B:C	40B:C	40B:C	40B:C	40B:C	20B:C	40B:C	4A:80B:C	20A:120B:C	20A:160B:C	80B:C	120B:C	160B:C
AS/NZ Model	N/A	A-581	N/A	N/A	N/A	N/A	A-580	N/A	N/A	N/A	A-564	N/A	N/A	A-564	N/A
AS/NZ Rating		2A:40B:E					40B:E				4A:80B:E			80B:E	
Shipping Wt.	14kg	19.2kg	26.3kg	19.2kg	26.3kg	14kg	19.2kg	19.2kg	26.3kg	14kg	19.2kg	26.3kg	14.2kg	19.2kg	26.3kg
Height	445mm	629mm	673mm	629mm	673mm	445mm	629mm	629mm	673mm	445mm	629mm	673mm	445mm	629mm	673mm
Width	267mm	267mm	279mm	267mm	279mm	267mm	267mm	267mm	279mm	267mm	267mm	279mm	267mm	267mm	279mm
Depth	178mm	178mm	203mm	178mm	203mm	178mm	178mm	178mm	203mm	178mm	178mm	203mm	178mm	178mm	203mm
Range	12m - 15m			12m - 15m			12m - 15m			12m - 15m			12m - 15m		
Discharge Rate (Ave.) (kg/sec)	0.4	0.5	0.65	0.4	0.8	0.4	0.4	0.9	0.85	0.27	0.3	0.4	0.27	0.31	0.4
Discharge time (sec)	15	18	21	15	17	15	15	10	16	22	30	34	22	29	34
Standard Bracket	Wall														