



Regular Dry Chemical

Manufactured and Tested to
ANSI/UL Standards
AS/NZ Standards
Amerex is an ISO-9001:2000
Registered Firm

- ★ Dependable Steel Cylinders
- ★ All Metal Valve Construction
- ★ Easy and less costly to maintain and service
- ★ U/L & U.S. Coast Guard Listed
- ★ Bar Coded Labels

Note: All extinguishers are U.S. Coast Guard approved with bracket listed on U.L. label.

Stored Pressure



AS & NZ Additional white band



REGULAR extinguishers contain a siliconized sodium bicarbonate based dry chemical with free flowing and non-caking additives. Economical Class B & C protection with lower initial cost and recharging. This chemical smothers fires in flammable liquids and pressurized gases and will not conduct electricity back to the operator.

Available in Wheeled and Stationary extinguishers.

6 YEAR WARRANTY

Specifications	REGULAR Dry Chemical								
	Aluminium					Brass, Chrome plated (No Alloy)			
Valves									
Size and Capacity	0.45kg	1kg	2.26kg	2.27kg	4.5kg Tall	9kg	2.27kg	4.5kg	9kg
Application	Nozzle					Hose and Nozzle			
Model Number	A620T	B403T	B409T	B453	B457	A412	B462	B447	408
U/L Rating	2B:C	10B:C	10B:C	40B:C	60B:C	120B:C	40B:C	60B:C	120B:C
AS/NZ Model	N/A	N/A	A-B409AS	N/A	A-B457AS	A-A412AS	A-404AS	N/A	A-408AS
AS/NZ Rating			30B:E		40B:E	80B:E	30B:E		80B:E
Shipping Wt.	1.13kg	2.26kg	4.2kg	4.3kg	8.2kg	17.2kg	6.2kg	8.6kg	17.7kg
Height	254mm	394mm	387mm	387mm	508mm	591mm	413mm	521mm	607mm
Width	89mm	146mm	140mm	184mm	186mm	260mm	216mm	222mm	260mm
Depth	70mm	76mm	108mm	108mm	127mm	178mm	108mm	108mm	178mm
Range	1.5m - 2.5m	2.75m - 4.5m	3.7m - 5.5m	3.7m - 5.5m	4.5m - 6.4m	4.5m - 6.4m	4.5m - 6.4m	4.5m - 6.4m	4.5m - 6.4m
Discharge time (sec)	10	10	10	14	18	28	14	18	28
Available with chrome plated cylinder	YES	YES	YES	YES					
F.M Approved		YES	YES		YES	YES	YES	YES	YES
Standard Bracket	Vehicle	Vehicle - Marine			Wall				